



Mobil DTE™ 20 Ultra Series

Mobil Industrial , United States

Hydraulic Oil



Product Description

Mobil DTE 20 Ultra series oils are high performance anti-wear hydraulic oils with extended oil life capabilities and have demonstrated up to 2 times longer oil drain intervals versus similar competitive oils (*).

They meet the stringent requirements of hydraulic systems using high pressure, high output pumps as well as other hydraulic system components such as close clearance servo-valves and numerically controlled (NC) machine tools. The products exhibit outstanding oxidation and thermal stability allowing long oil life and reduced deposit formation in harsh conditions and with severe hydraulic systems using high pressure, high output pumps. The keep clean performance helps protect critical hydraulic system components from malfunction, such as tight tolerance servo and proportional valves found in many modern hydraulic systems.

These products met the most rigorous performance requirements of a wide range of hydraulic system and component manufacturers, allowing use of a single product with excellent performance characteristics.

(*) with a viscosity index around 100 and a zinc-based anti-wear system - meeting at least ISO 11158 (L-HM) and/or DIN 51524-2 (HLP type) requirements.

Features and Benefits

Features	Advantages and Potential Benefits
Outstanding Keep Clean Performance	Reduced system deposits and sludge to help protect equipment and extend equipment life, reduce maintenance costs and improve total system performance
Enhanced Anti-wear Performance	Meets or exceeds major pump manufacturer requirements, helps extend component life
Exceptional Thermal and Oxidation Stability	Helps reduce maintenance downtime and costs by contributing to system cleanliness and deposit reduction even under harsh conditions
Enhanced Corrosion Protection	Helps ensure protection with a wide variety of component metallurgy
Controlled Demulsibility	Protects systems from small and large quantities of water and helps extend filter life
Quality Reserve	Maintains performance features even under severe service conditions and extended drain intervals

Applications

- Hydraulic systems critical to deposit build-up or where sludge and deposits form with conventional products.
- Hydraulic systems requiring a high load-carrying capability and anti-wear protection, and when thin oil-film corrosion protection is an asset.
- Where small amounts of water are unavoidable.

- Systems containing gears and bearings.
- Machines employing a wide range of components using various metallurgy.

Specifications and Approvals

This product has the following approvals:	MOBIL DTE 21 ULTRA	MOBIL DTE 24 ULTRA	MOBIL DTE 25 ULTRA	MOBIL DTE 26 ULTRA
BoschRexroth Fluid Rating List 90245		X	X	X
Denison HF-0		X	X	X
Denison HF-1		X	X	X
Denison HF-2		X	X	X
Eaton E-FDGN-TB002-E		X	X	X
Fives Cincinnati P-68		X		
Fives Cincinnati P-69				X
Fives Cincinnati P-70			X	
HOCNF Norway-NEMS, Black	X	X	X	X
Husky			X	

This product meets or exceeds the requirements of:	MOBIL DTE 21 ULTRA	MOBIL DTE 24 ULTRA	MOBIL DTE 25 ULTRA	MOBIL DTE 26 ULTRA
ASTM D6158 (Class HMHP)		X	X	X
China GB 11118.1-2011, L-HM(General)		X	X	X
China GB 11118.1-2011, L-HM(HP)		X	X	X
DIN 51524-2:2006-09	X	X	X	X
ISO L-HM (ISO 11158:2009)	X	X	X	X
JCMAS HK VG32		X		
JCMAS HK VG46			X	

Properties and Specifications

Property	MOBIL DTE 21 ULTRA	MOBIL DTE 24 ULTRA	MOBIL DTE 25 ULTRA	MOBIL DTE 26 ULTRA
Grade	ISO 10	ISO 32	ISO 46	ISO 68
Air Release Time, 50 C, min, ASTM D3427				
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130	1A	1A	1A	1A

Property	MOBIL ULTRA	DTE 21	MOBIL ULTRA	DTE 24	MOBIL ULTRA	DTE 25	MOBIL ULTRA	DTE 26
Density @ 15.6 C, kg/l, ASTM D4052	0.8373		0.8596		0.8667		0.8743	
Emulsion, Time to 3 mL Emulsion, 54 C, min, ASTM D1401	25		20		20		20	
FZG Scuffing, Fail Load Stage, A/8.3/90, ISO 14635-1			11		11		11	
Flash Point, Cleveland Open Cup, °C, ASTM D92	174		231		238		252	
Foam, Sequence I, Stability, ml, ASTM D892	0		0		0		0	
Foam, Sequence I, Tendency, ml, ASTM D892	20		10		10		10	
Foam, Sequence II, Stability, ml, ASTM D892	0		0		0		0	
Foam, Sequence II, Tendency, ml, ASTM D892	10		10		10		20	
Foam, Sequence III, Stability, ml, ASTM D892	0		0		0		0	
Foam, Sequence III, Tendency, ml, ASTM D892	20		10		10		0	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	2.8		5.8		7.1		8.9	
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	10.7		33.4		46.2		68.6	
Pour Point, °C, ASTM D97	-45		-36		-33		-30	
Rust Characteristics, Procedure B, ASTM D665	Pass		Pass		Pass		Pass	
Total Acid Number, mgKOH/g, ASTM D664	0.7		0.7		0.7		0.7	
Viscosity Index, ASTM D2270	106		115		110		104	

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2020

Exxon Mobil Corporation

22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved